



**NOTES**

**\*Material:**

- 1.Body: PPS UL 94V-0 Rated, Color:Black;
- 2.Cover: LCP UL 94V-0 Rated, Color:Black;
- 3.Contact: Phosphor Bronze;
- 4.Contact Plating: Gold Plating Over Nickel on Contact Area, Tin Plating on Solder Tail.

**\*Specification:**

- 1.Current Rating: 0.5 AMP. Max.;
- 2.Dielectric Withstanding Voltage: 500V AC R.M.S For One Minute;
- 3.Insulation Resistance: 1000 M Ohms Min. AT 500V AC;
- 4.Contact Resistance: 30 M Ohms Max.;
- 5.Operating Temperature: -25°C to +85°C;
- 6.Processing Temp: 245°C for 30~60 Seconds Max.;
- 7.Durability: 5000 Cycles.

**SCV-W2523X-06-LF**  
**LEADFREE**

**RoHS Compliant**

	PART NO. SCV-W2523X-06		CHECKED BY CY		TOLERANCES ARE .X ± 0.2 .XX ± 0.1 .XXX ± .AWG	DESCRIP TION: Sim Card 6Pin Without Post		
	DWG NO. SCV-W2523X-06		DRAWING BY			AREA	REVISIONS	HK
焜倫股份有限公司	FILE NO.		PROJECTION					
	UNIT / mm	SCALE 1:1						